

## Accessories

<b>JNIOR</b>	 <p><b>Rugged External Temperature Sensor</b></p>														
<b>Catalog Number</b>	<b>SEN-100-002</b>														
<b>Features</b>	<table border="0"> <tr> <td style="padding-right: 20px;"><b>Probe</b></td> <td>304 Stainless Steel</td> </tr> <tr> <td><b>Probe: Standard Length</b></td> <td>3 inches</td> </tr> <tr> <td><b>Cable: Standard Length</b></td> <td>12 feet (CAT 5)</td> </tr> <tr> <td><b>Pressure Tested</b></td> <td>Water Resistant to 60 PSI</td> </tr> <tr> <td><b>Environments</b></td> <td>Harsh</td> </tr> <tr> <td><b>Chemical Resistant</b></td> <td>YES</td> </tr> <tr> <td><b>Waterproof</b></td> <td>YES</td> </tr> </table>	<b>Probe</b>	304 Stainless Steel	<b>Probe: Standard Length</b>	3 inches	<b>Cable: Standard Length</b>	12 feet (CAT 5)	<b>Pressure Tested</b>	Water Resistant to 60 PSI	<b>Environments</b>	Harsh	<b>Chemical Resistant</b>	YES	<b>Waterproof</b>	YES
<b>Probe</b>	304 Stainless Steel														
<b>Probe: Standard Length</b>	3 inches														
<b>Cable: Standard Length</b>	12 feet (CAT 5)														
<b>Pressure Tested</b>	Water Resistant to 60 PSI														
<b>Environments</b>	Harsh														
<b>Chemical Resistant</b>	YES														
<b>Waterproof</b>	YES														
<b>Temperature</b>	<table border="0"> <tr> <td style="padding-right: 20px;"><b>Probe</b></td> <td>-67°F to 257°F (-55°C to 125°C)</td> </tr> <tr> <td><b>Cable</b></td> <td>-94°F to 302°F (-70°C to 150°C)</td> </tr> </table>	<b>Probe</b>	-67°F to 257°F (-55°C to 125°C)	<b>Cable</b>	-94°F to 302°F (-70°C to 150°C)										
<b>Probe</b>	-67°F to 257°F (-55°C to 125°C)														
<b>Cable</b>	-94°F to 302°F (-70°C to 150°C)														
<b>Accuracy</b>	<table border="0"> <tr> <td style="padding-right: 20px;"><b>-10°C to 85°C</b></td> <td>-0.5°C to 0.5°C</td> </tr> <tr> <td><b>-55°C to 125°C</b></td> <td>-2.0°C to 2.0°C</td> </tr> </table>	<b>-10°C to 85°C</b>	-0.5°C to 0.5°C	<b>-55°C to 125°C</b>	-2.0°C to 2.0°C										
<b>-10°C to 85°C</b>	-0.5°C to 0.5°C														
<b>-55°C to 125°C</b>	-2.0°C to 2.0°C														
<b>Dimensions</b>	<table border="0"> <tr> <td style="padding-right: 20px;"><b>Body Diameter (in.)</b></td> <td>.216 min - .220 max (.218 typical)</td> </tr> <tr> <td><b>Tip Diameter (in.)</b></td> <td>.218 min - .233 max</td> </tr> </table>	<b>Body Diameter (in.)</b>	.216 min - .220 max (.218 typical)	<b>Tip Diameter (in.)</b>	.218 min - .233 max										
<b>Body Diameter (in.)</b>	.216 min - .220 max (.218 typical)														
<b>Tip Diameter (in.)</b>	.218 min - .233 max														
<ul style="list-style-type: none"> <li>Contains RJ11 jack to plug directly into the JNIOR 1-Wire/Sensor Port</li> <li>Automatically recognized by the JNIOR software</li> <li>Submersible, Rugged, Wide Temperature Range Probe suitable for use in harsh environments</li> </ul>															