e information emp&channel=1)
when adding inputs to the state
end of a send. previously this was e.
MACRO NAME)
v key. default is -1
ol relay outputs 17 – 32 via the ASCII Client port. The format is as follows:
c y

Cinema.jar for Series 4 (410, 412) Release Notes

2.9.0	 + Added various calendar options to the Cinema Scheduling registry keys. The registry key follows the pattern AppData/Cinema/Schedule/xxxxx Where xxxxx can be any text. The new options are as follows: Daily,12:00,macro_name MoTuWeThFrSaSu,12:00,macro_name Monthly(15),12:00,macro_name Mar(15),12:00,macro_name Where 12:00 is the time to execute the macro in 24-hour format. Macro_name is the name of the macro to execute Any single day can be used, for example, Mo or Tu or any combination And day of the month can be used (1-31). Any month can be used Jan, Feb, Mar, Apr, May, Jun, Jul, Aug, Sep, Oct, Nov, Dec NOTE: The macro_name can be replaced with reboot (the JNIOR will reboot on that day and time) or reboota (reboots the JNIOR and erases the working RAM memory – you do not lose your programs or any configuration items)
2.8.0 11 Oct 2018	 RELEASED to Website November 21, 2018 + Added IO Query to the Cinema Server Client. A device can now make a connection to the Cinema Server Client port and send a command to request the status of the inputs or outputs. For example, sending rout1? will receive back either rout1=0 (for OFF) or rout1=1 (for ON). Sending din1? will receive back either din1=0 or din1=1
2.7.0 17 Sep 2018	+ The connection to any device will remain connected during the same macro if multiple actions are to the same device. The Cinema program previously would connect, send the command and disconnect for each command within the same macro. Now it is just one connection.

2.6.2 Including 2.6.1 2.6.0 6 Sep 2018	 ! The . ('period') in a macro name was causing the macro to not execute when the run macro name command was sent via the serial connection. Added the 'period' to the list of valid characters acceptable in a macro name. + Can now execute a macro via a php request. This was added so that a user can create their own custom web page with 'buttons' and when the button is clicked, it can cause a macro to be executed. The php request works in conjunction with the JNIOR registry. NOTE: Contact INTEG for sample web page code. ! Fixed an issue where if a macro file was changed and the JNIOR was soft rebooted, the updated macro file would not be backed up to flash memory. The file is now backed up. ! Fixed an issue with several of the built-in QSC DCP 300 commands where the length parameter was not getting set correctly.
2.5.3	RELEASED to Website August 15, 2018
Including 2.5.2 2.5.1	! Fixed an issue that was created in the 2.3/2.4 release regarding the pattern matching for commands starting with :: and using the + for relays 9 − 16
2.5.0	! Fixed an issue with relay output triggers for running macros
30 May 2018	
2.4.1	RELEASED to Website August 6, 2018
Including 2.3.5 2.3.4	+ Added new macro keys for JNIOR 412DMX power back-up – Power Lost, Ready, Restored.
	+ Added Application Data for DCP Configuration web page
2.3.2 2.3.1	+ Now logging when preshow connects
27.14. 2040	+ Implemented preshow masking input and output
27 Mar 2018	
27 Mar 2018	+ Implemented SNMP functionality
27 Mar 2018	
27 Mar 2018 2.2.1	+ Implemented SNMP functionality
	+ Implemented SNMP functionality ! Fixed a race condition starting the preshow client
2.2.1	 + Implemented SNMP functionality ! Fixed a race condition starting the preshow client RELEASED to Website June 8, 2017 + Changed the time synchronization so that the cinema program checks the JNIOR OS every hour for the correct time. This will allow the cinema program to adjust automatically for

2.2.0 14 Mar 2017	 + Added in the Application Watch Dog for the cinema program. By default the watch is set to false. When you change the key to true and reboot, the cinema program will communicate with the JNIOR operating system on a regular time basis. Should the cinema program not check-in within a set amount of time, the cinema program will restart. The default key is as follows: AppData/Cinema/Watchdog = false Change it to true and reboot to activate the watch dog. +Changed soft pulses to use input conditioning instead of inversion
2.1.4 20 Dec 2016	! Corrected an issue where the Send command in a macro was not working with the Dolby devices.
2.1.3 09 Nov 2016	+ Added back the slight pause before closing a connection when sending a packet to Raw Ethernet devices.
2.1.2 01 Aug 2016	! Imported a software class for debugging purposes in a previous version that needed to be removed.
2.1.1 25 Jul 2016	 + Updated the program so that inputs 9 – 12 on the JNIOR Model 414 will act as Triggers to start a macro. ! Fixed an issue where if somebody incorrectly formatted a logic statement in the Cinema Logic registry keys, the cinema program would crash.
2.1.0 06 Jun 2016	+ Added appinfo.ini so the Cinema program is displayed in the JNIOR DCP on the Configuration – Applications web page.
2.0.17	RELEASED to Website July 18, 2016
3/7/2016	+ Changed the program macro operation so that a 'separate software thread' is NOT automatically created when a communication command (device control) is executed in a macro. This was causing the macro to look like it failed, but in reality did not. If the macro or device requires that the command be spun off into a separate thread so that back to back actions can be executed quickly, a Registry Key in AppData/Cinema has been added to allow this feature to be enabled again. The default key is as follows: AppData/Cinema/ExternalMacroInSeparateThread = false Change it to true and reboot.
2.0.16	Minor adjustment for field testing

2.0.15	Minor adjustment for field testing
2.0.14	RELEASED to Website June 17, 2015
6/5/2015	! Fixed an issue where the hex format had the be entered in lower case
2.0.13 5/26/2015	 + Added new hex format to remove the "h " after every 2 characters. Can now enter them either way. With the word hex followed by the hex string with no spaces. For example, hex 52H 69H 63H 6BH OR hex 5269636B + Added Raw Udp Device
2.0.12 4/16/2015	+ Add delayed logic to all triggers
2.0.11 3/23/2015	+ Added a delayed emergency feature to make sure the fire alarm signal is present for a predefined period of time.
2.0.10	RELEASED to Website April 7, 2015
3/18/2015	! Fixed an issue where we were not logging messages from a Cinema Server Client
2.0.9 2/18/2015	! Fixed an issue sending input switch commands to the NEC projector
2.0.8 2/12/2015	! Fixed an issue where sending multiple macro commands at once to the Cinema Server Client port from a cinema server (GDC for sure) may not always execute. All macros are now properly executed.
2.0.7.260	RELEASED to Website February 4, 2015
4/Feb/2015	! Fixed an issue where a delay was accidentally left in the code thus slowing down macro execution in versions 2.0.5.254 and 2.0.6.258
2.0.6.258	RELEASED to Website January 21, 2015
21/Jan/2015	! Fixed an issue where the 'soft pulse' of a JNIOR digital input would not work.
	! Fixed an issue where any actions above 100 would not work (can have up to 200). Can now utilize all actions.
2.0.5.254	RELEASED to Website January 20, 2015
7/Jan/2015	! Changed the functionality where serial registry folders for Cinema Client and Cinema Server Client were not getting created unless the client method was set to serial. The serial folders are now created by default.

2.0.4.242	RELEASED to Website November 25, 2014
6/Oct/2014	+ Increased the total number of actions (not macros) that can be in one macro file to 200 actions.
	+ Added the ability to allow a cinema server to send the command 'reboot' to the Cinema Server Client port and the JNIOR will reboot.
	+ Added the ability to let an action in a macro contain less than whole second pulses for the relays. For example, a 0.5 second pulse is now valid
	! Fixed an issue where commands being sent too quickly to the Control Panel could cause a deadlock.
	! Fixed an issue with reading the messages coming in to the 'client' with a serial connection
1.3.0.76	RELEASED to Website March 20, 2014
3/18/2014	+ Added the ability to send UDP broadcasts by entering 255.255.255.255 for the IP address in the devices file.
1.2.0.68	Converted Cinema.JNIOR to run on the JNIOR Series 4 platform as Cinema.JAR file